

FINC	Doc. No.: FM12/PDS/ADL/025		
FINISH	Page 1 of 1		
Issue No.: 02	Issue Date: 04/07/2024	Rev. No.: 01	Eff. Date: 05/07/2024

ACMEBOND HMMM 72

DESCRIPTION:

Hexamethoxy methyl melamine 72 % active on precipitated silica. White free flowing powder.

PRODUCT SPECIFICATION:

Parameters	S	Specification		Reference Test Method
	Units	Min	Max	
Ash Content (at 800°C for 2 hrs.)	%w/w	23.0	29.00	QC/STP/U1/02
Active Ingredient	%	71.0	73.0	QC/STP/U1/35
LOD (at 105°C for 2 hrs.)	%w/w		5.00	QC/STP/U1/04
Sieve residue on 100 mesh	%w/w		0.1	QC/STP/U1/03
Free Formaldehyde	%w/w		0.20	QC/STP/U1/43

PACKAGING:

25 Kgs (nett) in Paper Bags with LDPE Inner Liner.

STORAGE:

1 years from the date of production provided

Preserved in cool and dry atmosphere in Closed original packaging.

OCCUPATIONAL SAFETY AND HEALTH INFORMATION:

Refer to Material Safety Data Sheets (MSDS) prior to using this resin.

Corporate Office:

Finorchem Limited 9E, Saket Apartment, 2 Ho Chi Minh Sarani, 9th Floor Kolkata-700 071 +91-33-40634254, Corporate@finorchem.com