

	FINORCHEM LIMITED			Doc. No.: FM12/PDS/ADL/005
	FINISHED PRODUCT- PDS			Page 1 of 1
	Issue No.: 02	Issue Date: 04/07/2024	Rev. No.: 01	Eff. Date: 05/07/2024

## FINOREX PB-518

### DESCRIPTION:

Alkyl phenolic heat reactive resin.

### PRODUCT SPECIFICATION:

S.No.	Property	Unit	Specification		Test Method
			Min	Max	
1.	Appearance	-	Light yellow to yellow lumps		Visual
2.	Softening point (R&B)	°C	90	100	ASTM E28
3.	Methylol content	%	14	17	QC/STP/U2/115
4.	Gardner colour	-	-	6	ASTM D1544

### RECOMMENDED APPLICATIONS:

Finorex PB-518 gives good tack, open time and heat resistance. It imparts the required colour to the adhesive. It is recommended in adhesive formulations using Polychloroprene, SBR, NBR and Natural Rubber.

### PACKAGING:

25 Kg in paper bag with HDPE liner/ Paper drum packing.

### STORAGE:

Finorex PB-518 is a stable resin and can be stored for 12 months from the date of manufacture under normal storage conditions. Store below 35°C in tight container away from heat and humidity. Pallets should not be stored double stacked.

### OCCUPATIONAL SAFETY AND HEALTH INFORMATION:

Refer to Material Safety Data Sheets prior to using this resin.

#### Corporate Office :

Finorchem Limited  
9E, Saket Apartment, 2 Ho Chi Minh Sarani,  
9<sup>th</sup> Floor Kolkata-700 071  
+91-33-40634254, Corporate@finorchem.com